



SPECIFICATIONS ON OPPOSITE SIDE.



01 Light Blue




02 Royal Blue



03 Red



04 White



05 Orange



06 Yellow



08 Tan




09 Gray



10 Maroon



11 Purple



12 Black



13 Navy Blue



14 Kelly Green



15 Dark Green



15 OUNCE, DOUBLE-COATED
LAMINATED VINYL

porter[®]
www.PorterAthletic.com



Fabric Specifications

Total Weight: 15oz/yd²

Testing Method: ASTM D3776

Base Fabric:

9 x 9 x 1,000 Denier Polyester

Grab Tensile (lb/in):
228(w) x 203(f)

Testing Method: ASTM D751

Trapezoidal Tear (lb):
71(w) x 45(f)

Testing Method: ASTM D751

Adhesion (lb/in): 15(w) x 22(f)

Testing Method: ASTM D751




Flame Retardancy

NFPA 701: **Pass**

ASTM E84: **Class A**

CA Title 19-1237.1: **Pass**

CAL/ULC-S 109-03 LG & SM: **Pass**



Composition

Lead, phthalate, latex, and BPA free

CPSIA compliant

California Prop 65 compliant

porter®

150Z VINYL

DOUBLE-COATED, LAMINATED

Porter uses a heavy-duty 15oz vinyl on several specialty pad applications. The durable leather embossed finish is tear & abrasion resistant. Available in 14 UV resistant stock colors to compliment and coordinate with any school colors.

Features:

- Tear & Abrasion Resistant
- Rot & Fungus Resistant
- Mildew Resistant
- Dimensionally Stable
- Shrink Resistant
- UV Resistant



Applications:

Specialty Pads
Volleyball Padding

*reference Porter technical product documents
for designated vinyl specifications