


1792 POWR-STEEL VOLLEYBALL SYSTEM

SLEEVE-TYPE 3" OD STEEL VOLLEYBALL CENTER STANDARD



PARTS LIST - No. 1792			
No.	QTY.	DESCRIPTION	
1	1	UPRT 1791W	STEEL WINCH UPRIGHT
2	1	WINH 00113	POWR-SELECT WINCH
3	1	WINH 00114	CRANK FOR POWR-SELECT WINCH

- 1792 POWR-STEEL 3" VOLLEYBALL CENTER STANDARD (EACH)
- 17929XX POWR-STEEL 3" VOLLEYBALL CENTER STANDARD WITH PAD (EACH)
- 17929XXSP POWR-STEEL 3" VOLLEYBALL CENTER STANDARD WITH GRAPHIC PAD (EACH)

QTY	PART No.	DESCRIPTION	No.	PAGE No.
	VARIOUS	3 1/2" DIA FLOOR SLEEVE (EACH)	B	VARIOUS
	2295	UNIVERSAL VOLLEYBALL NET (EACH)	C	V-2295
	2297	POWR-SELECT NET ANTENNA (PAIR)	D	V-2297
	00546000	BOUNDARY MARKERS w/ ANTENNA (PAIR)	E	V-546
	8391XX	UPRIGHT CENTER PROTECTIVE PAD (EACH)	F	V-839

Porter[®]

888-277-7778 PORTER@PORTERATHLETIC.COM
© COPYRIGHT 2020 PORTER ATHLETIC - ALL RIGHTS RESERVED

PROJECT NUMBER

PROJECT NAME

Porter

WWW.PORTERATHLETIC.COM/FACILITY

VOLLEYBALL SPECIFICATION SHEET

V-1792

02/27/2020

1792 POWR-STEEL VOLLEYBALL SYSTEM

SLEEVE-TYPE 3" OD STEEL VOLLEYBALL CENTER STANDARD

SPECIFICATIONS

PORTER No. 1792 POWR-STEEL **VOLLEYBALL CENTER STANDARD (EACH)**

Standard shall be designed for multiple court use when used in conjunction with No. 1791 Powr-Steel volleyball end standards.

Volleyball post shall consist of one telescoping type uprights and one winch. Post shall be designed with height adjustment settings to meet all USAV, NCAA and NFHS requirements for competition. Aluminum posts, or posts that do not telescope (that extend above the top of the net) will not be approved as equal.

Bottom upright shall be 3" (7.62cm) O.D. high strength 6Ga steel. Upright shall be designed to fit standard 3" (7.62cm) floor sleeves for new construction or existing floors. Specify No. 790 or 792 type floor sleeve. Upright shall be powder coated in a corrosion resistant navy blue. Bottom of upright shall be provided with a special adjustable rubber foot to protect finished floors when moving standard. Rubber foot shall adjust in height to accommodate ground sleeves installed too deep. Net tie offs shall be welded on for additional tensioning strength.

Upper telescoping (adjustable) upright shall be 2 1/2" (6.35cm) O.D. 11 Ga plated steel. Upper end of the upright shall be equipped with a pulley to reduce cable drag and undue tension on the entire system. Pulley to be made of cast iron for additional strength and stability. Upper telescoping upright shall be adjustable in height by means of a high strength pull pin, and shall be furnished with cut out markings for the following heights:

AGE GROUPS	FEMALE/REVERSE CO-ED	MALE/CO-ED
70 years and above	2.19 m (7'-2 1/8")	2.29 m (7'-6")
55 years and above	2.19 m (7'-2 1/8")	2.38 m (7'-9 5/8")
45 years and above	2.19 m (7'-2 1/8")	2.43 m (7'-11 5/8")
15-18 years and under	2.24 m (7'-4 1/8")	2.43 m (7'-11 5/8")
13-14 years and under	2.24 m (7'-4 1/8")	2.24 m (7'-4 1/8")
11-12 years and under	2.13 m (7'-0")	2.13 m (7'-0")
10 years and under	1.98 m (6'-6")	2.13 m (7'-0")

Tensioning reel shall be a vertical lift, worm gear winch with steel frame. Frame construction shall be of interlocking steel for high rigidity and precise alignment, semi enclosed for safety, and powder coated for corrosion resistance. Self-locking worm drive will prevent snap back or loss of tension. Net shall attach directly to the winch eliminating the need for straps.

1792 upright shall consist of one winch post.

Weight of post shall not exceed 55 pounds.

WARRANTY

Volleyball system furnished with the following warranty:

Uprights – 10 year limited warranty

Winch – 1 year limited warranty

ISSUED FEBRUARY 27, 2020, SUBJECT TO CURRENT MANUFACTURING PROCEDURES AND CHANGES

COPYRIGHT 2020 - PORTER ATHLETIC - ALL RIGHTS RESERVED

PORTER@PORTERATHLETIC.COM

porter
WWW.PORTERATHLETIC.COM/FACILITY

VOLLEYBALL SPECIFICATION SHEET

V-1792

02/27/2020