

porter
www.porterathletic.com/facility


WALL MOUNT SPECIFICATION SHEET

10/1/2015

Diagram illustrating the wheelbarrow structure with dimensions:

- Overall width: 5'-6" (1.68m)
- Distance from centerline to each side: 2'-9" (83.8cm)
- Centerline is labeled: C BACKS TOP

AND GOAL No.



PROJECT NUMBER

PROJECT NAME

00312-000 - WALL-MOUNTED BACKSTOP

CENTER-STRUT® WALL-MOUNTED BACKSTOP
FOR RECTANGULAR BACKBOARD 6" and 1'-0" EXTENSIONS

SPECIFICATIONS

PORTER No. 00312-_____ CENTER-STRUT® WALL BRACED BACKSTOP FOR
RECTANGULAR BACKBOARD

Backstop shall be wall-braced type. Backstop shall be available in two extensions, with face of backboard extended 6" from supporting wall, or 1'-0" from supporting wall. Specify 6" or 1'-0" extension.

Extension frames shall be fabricated of three (3) 1-7/8" O.D. tubes. Both ends of extension frame assemblies shall terminate in heavy steel flanges for attachment to backside of backboard and wall pad attachments. Goal shall mount directly through the backboard and into a heavy steel flange Center-Strut® at the lower extension frame to eliminate any strain on the backboard, should a player hang on the front mounted goal.

Southern yellow pine wall pads shall be provided at all wall attachment points. All edges shall be chamfered and pads shall be finished with two finish coats of natural gloss lacquer.

All metal parts shall be painted one (1) coat of flat black enamel. (If special painting of colors is required, specify final painting by painting contractor.)

Specify backboard and goal as required.